## **CLAIM LISTING**

## IN THE CLAIMS

This listing of the claims will replace all prior versions, and listing, of claims in the application or previous response to office action:

1. **(Currently Amended)** A method for recovering from a failure event on a communication path between an information handling system and a sequential storage device, comprising:

monitoring the communication path during an information <u>data</u> exchange for a failure event;

marking, in response to detection of a failure event, <u>indicating</u> a <u>point location</u> in the information data exchange at which the failure event occurred; and

initiating a continuation of the information <u>data</u> exchange from the <u>point location</u> of failure on a fail-over communication path between the information handling system and the sequential storage device.

- 2. (Currently Amended) The method of Claim 1, further comprising marking indicating the point location of failure in a host bus adapter of the information handling system.
- 3. (Currently Amended) The method of Claim 1, further comprising marking indicating the point location of failure in the sequential storage device.
- 4. **(Currently Amended)** The method of Claim 1, further comprising communicating the **point** <u>location</u> of failure to a fail over host bus adapter on the information handling system using a support driver.
- 5. (Currently Amended) The method of Claim 1, further comprising including an originator exchange identifier, a receiver exchange identifier and a port identifier in the marking indicating of the point location of failure.

PATENT APPLICATION 10/769,583

ATTORNEY DOCKET 016295.1530 (DC-05847)

3

- 6. (Currently Amended) The method of Claim 1, further comprising querying the sequential storage device by the information handling system for identification of its marking indicating point location of failure.
- 7. (Currently Amended) The method of Claim 6, further comprising initiating continuation of the information <u>data</u> exchange based on sequential storage device query results.
- 8. (Currently Amended) The method of Claim 1, further comprising passing a pointer to a buffer including contents of the information <u>data</u> exchange from a host bus adapter associated with the failed communication path to a fail over host bus adapter associated with a fail over communication path.

9. (Currently Amended) Software for completing a transaction between a sequential storage device and a host information handling system after a failure event on a communication path between the sequential storage device and the host information handling system, the software embodied in computer readable media and when executed operable to:

detect a failure event on the communication path;

retain information concerning at least one open exchange being communicated on the communication path;

retrieve an exchange status indicating a **point location** in the **information data** exchange at which the failure event occurred; and

continue communication of the exchange based on the exchange status on a fail over path between the host information handling system and the sequential storage device.

- 10. (Currently Amended) The software of Claim 9, further operable to query the sequential storage device for the exchange status indicating the <u>location</u> in the <u>information</u> <u>data</u> exchange at which the failure event occurred.
  - 11. (Original) The software of Claim 9, further operable to:

read open exchange information from a host bus adapter associated with the failed communication path; and

communicate the open exchange information to a host bus adapter associated with the fail over communication path.

- 12. (Original) The software of Claim 9, further operable to monitor continued communication of the exchange for an acknowledgment of exchange completion.
- 13. (Original) The software of Claim 9, further operable to buffer data received in the exchange communication at the sequential storage device.
- 14. (Original) The software of Claim 9, further operable to retain information concerning at least one open exchange on the host information handling system and the sequential storage device.

15. (Currently Amended) An information handling system, comprising:

at least one processor;

a memory operably coupled to the processor;

at least one communication device operably coupled to the processor and the memory, the communication device operable to communicate data on at least one communication path; and

a program of instructions storable in the memory and executable by the processor, the program of instructions operable to **mark indicate** a **point location** of failure in an information **data** exchange with a sequential storage device in response to a communication path failure and facilitate communication of the information **data** exchange with the sequential storage device from the **point location** of failure on a fail over communication path.

- 16. (Currently Amended) The information handling system of Claim 15, further comprising the program of instructions operable to respond to a query concerning the information <u>data</u> exchange <u>point location</u> of failure.
- 17. (Currently Amended) The information handling system of Claim 15, further comprising the program of instructions operable to query the sequential storage device to identify the information data exchange point location of failure.
- 18. (Currently Amended) The information handling system of Claim 15, further comprising the program of instructions operable to communicate data concerning the information <u>data</u> exchange to communication hardware associated with the fail over communication path.
- 19. (Currently Amended) The information handling system of Claim 15, further comprising the program of instructions operable to include at least an originator exchange identifier and a receiver exchange identifier and marking indicating the point location of failure of the information data exchange.

- 20. (Original) The information handling system of Claim 15, further comprising:
- a first host bus adapter operable to communicate with the sequential storage device along a first communication path;
- a second host bus adapter operable to communicate with the sequential storage device along a second communication path; and
- at least one host bus adapter operable to retain an exchange state for at least one open exchange being communicated on an associated communication path.
- 21. (Currently Amended) The information handling system of Claim 15, further comprising:
- a fibre channel interface module operable to receive at least one information <u>data</u> exchange on a communication path; and

the fibre channel interface module operable to retain an exchange state for at least one open exchange communicated on the communication path.